



Prefinished Hardwood Flooring™



GENERAL SPECIFICATIONS

Characteristics	Solid
Description	<ul style="list-style-type: none"> • Solid prefinished hardwood flooring with tongues and grooves • Micro-V bevel (on 4 sides)
Thickness	3/4"
Width	3 1/4"
Length	Random lengths from 10" to 76"
Installation	Nailed or stapled down (on or above grade)
Species	2 species: Red Oak, Maple
Grade	Character floors: These floors are appreciated for their pronounced color variation. They feature open and closed knots, mineral streaks, cracks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment.
Color choice	8 colors: Espresso, Gray, Gunstock, Mocha, Natural, Saddle, Stone, Whiskey
Finish	Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane. Semi-Gloss (50% gloss) or Opal (18% gloss)
Applicable standards	Static Friction Coefficient (ASTM-D-2047): Slippery resistance of 0.5 to 0.55 Surface Burning (ASTM-E-84): <ul style="list-style-type: none"> • FSI (Flame Spread Index) 100 to 150 Class C (depends on wood species) • SD (Smoke Development) 75 to 400 (depends on wood species) Surface Burning (ULC-S-102-2): <ul style="list-style-type: none"> • FSV (Flame Spread Value) 100 to 150 (depends on wood species) • SD (Smoke Development) 200 to 300 (depends on wood species) Critical radiant flux (ASTM-E-648-94a): 0.25 to 0.40 watt/cm ² (depends on wood species) R value: R 0.6 to 0.8 (depends on wood species) Formaldehyde and VOC emissions (CDPH 1.1, 2010) : Target product group conform UV protection
Provenance	Made in St-Georges, Qc, Canada.
Use	Residential, light commercial
Accessory	Round Stair nosing, Round reducer, Multifunction reducer, Threshold, "T" molding, Quarter round
Warranty	<ul style="list-style-type: none"> • Lifetime limited structural warranty (Relative humidity must always be maintained within a range of 35% and 55%). • 25-year finish warranty for residential applications
Packaging	3 1/4"
Content of a box Size of a box Weight of a box Content of a pallet Size of a pallet	20 sq. ft. 79" L x 10-1/2" W x 3-1/4" H 49 to 60 lbs 48 boxes = 960 sq. ft. (4 boxes/W x 12 boxes/H) 79" L x 42" W x 42" H
Relative species hardness	
NWFPA Janka Test Hardness test (ASTM-D-143) Red Oak 1,290 lbs* - 100% *lbs = Applied force in pounds	Red Oak 1,290 lbs - average hardness Maple 1,450 lbs - 12% harder